

Ultralow Quiescent, Fast Transient Low Dropout Regulator

■ FEATURES

- Low Quiescent Current: 1.6 μ A
- High Input Voltage: Up to 35V
- High Output current: 200mA
- Without Overshoot in Start Up
- Without Overshoot after Short Circuits Removed
- Low Dropout Voltage: 280mV@100mA,
580mV@200mA
- Fixed Output Voltages: 3.3 and 5.0V
- High-accuracy Output Voltage: $\pm 2\%$
- Good Transient Response
- Low Temperature Drift: ± 100 ppm/ $^{\circ}$ C
- Integrated Short-Circuit Protection
- Integrated Thermal Protection
- Available Packages : SOT23-3

■ DESCRIPTION


The AIC1703B series is a high voltage, ultralow-power, low dropout voltage regulator. The device can deliver 100mA output current with a dropout voltage of 300mV and allows an input voltage as high as 35V. The typical quiescent current is only 1.6 μ A. The device is available in fixed output voltages of 3.3 and 5.0V. The device features integrated short-circuit and thermal shutdown protection.

Although designed primarily as fixed voltage regulators, the device can be used with external components to obtain variable voltages.

■ APPLICATIONS



- Battery-powered equipment
- Portable equipment
- Audio/Video equipment

■ TYPICAL APPLICATION CIRCUIT



AIC1703B Typical Application Circuit

ORDERING INFORMATION



Example: AIC1703B-33GU3TR
 → 3.3V Version, in Green SOT23-3
 Package and Tape & Reel Packing
 Type

● **Marking**

Part No	Marking
AIC1703B-XXGU3	53XXB

(XX: output voltage (33=3.3V, 50=5.0V); B: output accuracy ±2%)

ABSOLUTE MAXIMUM RATINGS

VIN Pin to GND Pin Voltage	-0.3V to 35V
VOUT Pin to GND Pin Voltage	-0.3V to 6V
VOUT Pin to VIN Pin Voltage	-35V to +0.3V
Peak Output Current	Internally Limited
Storage Temperature Range	-40°C~150°C
Lead Temperature (Soldering, 10 sec)	260°C
Operating Virtual Junction Temperature	150°C
Operating Ambient Temperature Range	-40°C~85°C
Thermal Resistance Junction to Ambient, θ_{JA} SOT23-3	400°C/W
Power Dissipation, P_D SOT23-3	0.25W
(Assume no Ambient Airflow, no Heatsink)	

Absolute Maximum Ratings are those values beyond which the life of a device may be impaired.

■ ELECTRICAL CHARACTERISTICS
($T_A=25^\circ\text{C}$, $C_{IN}=1\mu\text{F}$, $V_{IN}=V_{OUTNOM}+1.0\text{V}$, $C_{OUT}=10\mu\text{F}$, unless otherwise specified) (Note 1)

PARAMETER	TEST CONDITIONS	SYMBOL	MIN.	TYP.	MAX.	UNIT
Input Voltage		V_{IN}			35	V
Quiescent Current	No Load	I_{GND}		1.6	2.0	μA
Output Voltage	$I_{OUT}=10\text{mA}$	V_{OUT}	$V_{OUTNOM}^* 0.98$	V_{OUTNOM}	$V_{OUTNOM}^* 1.02$	V
Output Current		I_{OUT_MAX}	200	250		mA
Dropout Voltage (Note 2)	AIC1703B-50, $I_{OUT}=100\text{mA}$, $\Delta V_{OUT} = -V_{OUTNOM} * 2\%$	V_{DROP}		280	350	mV
	AIC1703B-50, $I_{OUT}=200\text{mA}$, $\Delta V_{OUT} = -V_{OUTNOM} * 2\%$			580	700	
	AIC1703B-33, $I_{OUT}=100\text{mA}$, $\Delta V_{OUT} = -V_{OUTNOM} * 2\%$			300	380	
	AIC1703B-33, $I_{OUT}=200\text{mA}$, $\Delta V_{OUT} = -V_{OUTNOM} * 2\%$			600	750	
Load Regulation	$1\text{mA} \leq I_{OUT} \leq 100\text{mA}$	ΔV_{OUT}		20	50	mV
Line Regulation	$I_{OUT} = 1\text{mA}$, $V_{IN}=(V_{OUTNOM}+1\text{V})$ to 35V	$\frac{\Delta V_{OUT} * 100}{\Delta V_{IN} * V_{OUT}}$			0.2	%/V
Current Limit	$V_{IN}=(V_{OUTNOM}+1\text{V})$ to 35V, $R_{LOAD}=V_{OUTNOM}/1\text{A}$	I_{LIMIT}		450		mA
Thermal Shutdown Threshold		T_{SHDN}		125		$^\circ\text{C}$

Note 1. Specifications are production tested at $T_A=25^\circ\text{C}$. Specifications over the -40°C to 85°C operating temperature range are assured by design, characterization and correlation with Statistical Quality Controls (SQC).

Note 2. Dropout Voltage is the voltage difference between the input and the output at which the output voltage drops 2% below its nominal value.

■ TYPICAL PERFORMANCE CHARACTERISTICS




Fig. 1 Startup




Fig. 2 Startup




Fig. 3 Load Transient Response




Fig. 4 Line Transient Response




Fig. 5 Short-Circuit Occurred





Fig. 6 Short-Circuit Removed

■ BLOCK DIAGRAM


Functional Block Diagram of AIC1703B

■ PIN DESCRIPTION

- VIN - Regulator input supply pin.
- GND - Ground pin.
- VOUT - Regulator output pin.

■ APPLICATION INFORMATION

Power Dissipation

The power dissipated by the p-channel MOSFET

$$P_{D(\text{MOSFET})} = (V_{\text{IN}} - V_{\text{OUT}}) * I_{\text{OUT}}$$

Total Power Dissipation

$$P_{D(\text{TOTAL})} = P_{D(\text{MOSFET})} + V_{\text{IN}} * I_{\text{GND}}$$

The quiescent current I_{GND} is only 1.6 μA , so that

$V_{\text{IN}} * I_{\text{GND}}$ can be ignored. The maximum power dissipation can be estimated by

$$P_{D(\text{max})} = [V_{\text{IN}(\text{max})} - V_{\text{OUT}(\text{min})}] * I_{\text{OUT}}$$

Junction Temperature

$$T_{\text{J}} = P_{D(\text{max})} * \theta_{\text{JA}} + T_{\text{A}}$$

θ_{JA} is thermal resistance of junction to ambient,

T_{A} is the ambient temperature.

■ APPLICATION EXAMPLES




Fig. 7 Application Circuit for Increasing Output Voltage









Fig. 8 Application Circuit for Increasing Output Voltage

■ PHYSICAL DIMENSIONS
● SOT23-3


SEE VIEW B



SOT23-3		
MILLIMETERS		
SYMBOL	MIN.	MAX.
	A	0.95
A1	0.00	0.15
A2	0.90	1.30
b	0.30	0.50
c	0.08	0.22
D	2.80	3.00
E	2.60	3.00
E1	1.50	1.70
e	0.95 BSC	
e1	1.90 BSC	
L	0.30	0.60
L1	0.60 REF	
θ	0°	8°

- Note: 1. Refer to JEDEC MO-178.
 2. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion or gate burrs shall not exceed 10 mil per side.
 3. Dimension "E1" does not include inter-lead flash or protrusions.
 4. Controlling dimension is millimeter, converted inch dimensions are not necessarily exact.

Note:

Information provided by AIC is believed to be accurate and reliable. However, we cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in an AIC product; nor for any infringement of patents or other rights of third parties that may result from its use. We reserve the right to change the circuitry and specifications without notice.

Life Support Policy: AIC does not authorize any AIC product for use in life support devices and/or systems. Life support devices or systems are devices or systems which, (i) are intended for surgical implant into the body or (ii) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.